

Door/Window Sensor Installation Guide

IMPORTANT: You will need to put your system on test mode before you begin your installation. This is to ensure authorities are not sent due to an accidental alarm going off.

Go to <u>www.guardianprotection.com</u> and log into your Guardian account. Select "testing my system" on the right-hand side. Then simply follow the steps provided. Your system will be on test mode for 4 hours.

For this installation you will need your Master Panel Code and may need a step ladder.

Programming Your New Sensor

- 1 Remove the two pieces of your sensor from the box. The larger piece is the sensor, and the smaller piece is the magnet.
- **2** Go to your home security panel.
- 3 Select the top menu bar. Select `Settings.'
- **4** Select 'Advanced Settings' and enter in your master
- 5 Select `Security Sensors' and then `Auto Learn.'
- 6 Pull out the battery tabs from the new sensor. This will auto-learn the sensor into your security system. You will receive a notification on your panel once this is complete. Select OK.
- 7 Assign a zone group to your sensor from the drop-down menu. You can choose delay group #10 or perimeter group #13. Delay group #10 gives you some time to enter or leave your home without setting off the alarm. Perimeter group #13 goes into an immediate alarm when the sensor is opened, with no delay.



8 Name the sensor from the top right corner using the drop-down menu. Then select "Add New." You'll receive another notification from the panel that the sensor was added successfully.

Next, you'll need to perform a cellular test on your security panel to ensure your new device is communicating properly with Guardian Protection.

Test Cellular Status



- Select the top menu bar
- Select `Settings'
- 3 Select `Advanced Settings," then enter your Master Panel Code
- 4 Select 'System Tests'
 - Select *`Cellular* Test'
 - Select the `Start' button



Installing Your New Sensor



Step 7

- 1 Thoroughly clean the surface where you will be placing the new sensor.
- **2** Peel and stick the adhesive tape to the back of the sensor and the magnet.
- 3 Mount the sensor with the magnet indicator pointing toward the magnet location. **NOTE**: Make sure that the arrows on the transmitter and the magnet are aligned.
- **4** Mount the magnet pointing toward the door sensor indicator.
- **5** Press and hold the pieces in place for 20 seconds.
- 6 Open and close the door a few times to make sure the pieces don't shift, bump one another, or fall off.
- 7 Next, arm your system in Away mode and open the door or window so the sensor triggers an alarm (don't worry; your system will still be in test mode). This will ensure the new sensor is communicating properly. This will also initiate a system test to ensure the new sensor and system are communicating properly.

That's it! You're all set. Return to your online Guardian account or contact us at **1.800.PROTECT** (1.800.776.8328) to remove your system from Test Mode.